

# DERBISILVERTOP S

*Bituminous aluminium protective coating*



## Description

- ▶ DERBISILVERTOP S is a modified-bitumen-based aluminium coating designed for the renovation and maintenance of dried-out roofs, sheet iron, steel or aluminium decks, fibre-cement sheets and old bituminous roofing membranes.

## Advantages

- ▶ The regeneration and waterproofing of old roofs
- ▶ Provides an effective heat shield, reducing surface temperature considerably
- ▶ Quick drying, retaining its flexibility
- ▶ Revitalises the roof –after repairs- a nice aesthetic aluminum look
- ▶ Adheres to porous and dry surfaces
- ▶ Provides effective protection against corrosion and moss development
- ▶ Seals minute cracks
- ▶ Improves the quality of recycled rainwater.

## Usage

Consumption :	according to the nature and the condition of the surface : ± 0,3 l/m <sup>2</sup> on metal ± 0,4 l/m <sup>2</sup> on roofing ± 0,5 l/m <sup>2</sup> on concrete and fibre-cement
Equipment :	brush
Cleaning material :	white spirit
Drying time :	rain proof within 24 hours

## Packaging

Can of :	4 l 10 l 20 l
----------	---------------------

## Technical data

Density :	1,03 kg/l
Non volatiles :	63 %
Flashpoint Pensky Martens cc :	27 °C

## Storage

In airtight cans, in a well-ventilated place, away from any heat source.

