

DERBIFILL S

Bituminous mass for slopes and levelling



Description

- ▶ DERBIFILL S is the ideal product for the levelling of roofs and for rectifying counterslopes and depressions.

Advantages

- ▶ Prevents puddle formation
- ▶ Rectifying the surface eases the application of the waterproofing membrane
- ▶ Economical solution for roof levelling
- ▶ Ensures optimum adhesion between bituminous waterproofing products and substrate
- ▶ Ready-to-use product
- ▶ Can be applied up to a thickness of 50 mm
- ▶ Sets quickly
- ▶ Malleable and practical
- ▶ Prevents water stagnation around domes and skylights.

Usage

- Consumption : varies depending on the nature and type of application.
As a guide : 100 cm x 100 cm x 1 cm (depth) = 10 litres volume \approx 10 kg
- Equipment : trowel
- Cleaning material : white spirit
- Drying time : 24 hours

Packaging

- Can of : 25 kg, provided with polyethylene ECO-bag, keeping the can clean both during and after use, limiting chemical waste to only the ECO-bag

Technical data

- Density : 1 kg/l (practical density for application)
- Non volatiles : 96,5 %
- Flashpoint Pensky Martens cc : 1 °C

Storage

- In airtight cans, in a well-ventilated place, away from any heat source.

This document cancels and replaces any other document published previously.
All values shown are nominal and subject to normal manufacturing tolerances.



WWW.DERBIGUM.COM



IMPERBEL sa/nv
Bergensesteenweg 32 – B-1651 Lot
Tel.: 02 334 87 00
Fax: 02 378 14 69
E-mail: infobe@derbigum.com